MMFRMM Returno



Shown almost actual size!

Compact Four Input Dante Interface

- Four independent channels.
- On each channel:

Balanced line input with two gain settings (+4dBu or -10dBv) on XLR or $\frac{1}{4}$ "TRS.

Switch selectable to...

High headroom Instrument DI with two gain settings for passive & active pickups on $\frac{1}{4}"$ TS.

- Inputs 3-4 can be switched to accept an S/PDIF input.
- Power is supplied via POE (power over ethernet) or available external power brick.
- Two Inferno Returnos can be chained together, allowing eight inputs on a single ethernet cable. Interconnection is accomplished by short ethernet cable and power jumper.
- Inferno Returno solves many challenges encountered in the studio or on stage: multiple stereo output keyboard rigs, stereo guitars with fx and direct sends, legacy analog mic preamps, wireless mic receivers, electronic drums...

AudioSimplified

Inferno Returno Specs:

Line Inputs (balanced or unbalanced):

Input connector: XLR or $\frac{1}{4}$ " TRS Impedance: 48k Ω differential Nominal/Maximum Level norm: +4dBu / +24dBu Nominal/Maximum Level boost: -10dBv / +12dBu

Direct Instrument Inputs(DI) (unbalanced):

Input connector: $\frac{1}{4}$ " TS Impedance: 4.7megohm Nominal/Maximum Level norm: -26dBu / -6dBu Nominal/Maximum Level boost: -6dBu / +14dBu

Noise level:

-96 dBa

Distortion:

THD: .026% IMD: .032%

Power:

POE: 4500mw,class 0 – one unit powered POE: 9800mw,class 0 – two units powered External: 48v,300ma, 1500v ISO certified Aux Power Output: 48v, 150ma max for loop to second Inferno Returno. Optional cable required.

Dimensions:

width: 4" (101.5mm)
height: 2" (50.9mm)
depth: 6.14"(156mm)

Dante:

Sample Rates: 44.1k, 48k (96k coming soon)
Ports: (1)POE/Dante, (1)Dante for daisy chain

Introductory Price:

Inferno Returno: \$390.00 Chain cables(enet + power): \$18.00 External Power Supply (optional): \$30.00

> ©2021 Audio Simplified LLC Jim Mikles 6401 Hickory Overlook, Columbia, MD 21044 audio-simplified.com 410.999.0918